



## Mobil Special™

Mobil Passenger-Vehicle-Lube , 中国

### Product Description

Mobil Special™ is a range of high performance gasoline motor oils that deliver engine protection and cleanliness. Mobil Special is recommended for use in a wide range of applications and operating conditions. Suitable for use in passenger car application using gasoline, CNG or LNG.

### Features and Benefits

- Helps reduce engine wear and corrosion
- Helps keep engine clean
- Multigrade motor oil allowing easier starts at low temperatures
- Good high temperature properties

### Specifications and Approvals

|   |   |
|---|---|
| <b>Mobil Special meets the requirements of:</b> |   |
| API SL  | X |

### Typical Properties

| Mobil Special      | Test Method | Unit |                  |                  |                  |                  |
|--------------------|-------------|------|------------------|------------------|------------------|------------------|
| SAE Grade          |             |      | 5W-30            | 10W-30           | 15W-40           | 15W-50           |
| Appearance         | Visual      |      | Bright and Clear | Bright and Clear | Bright and Clear | Bright and Clear |
| Viscosity @ 100 °C | ASTM D445   | cSt  | 10.3             | 10.5             | 13.7             | 18.7             |
| CCS Viscosity      | ASTM D5293  | cP   | 5900 @ -30°C     | 6000 @ -25°C     | 5600 @ -20°C     | 6400 @ -20°C     |
| Sulfated Ash       | ASTM D874   | wt%  | 0.8              | 0.8              | 0.8              | 0.8              |
| Flash Point        | ASTM D92    | °C   | 223              | 220              | 230              | 250              |
| Pour Point         | ASTM D97    | °C   | -36              | -25              | -30              | -30              |
| Zinc               | ASTM D4951  | wt%  | 0.11             | 0.11             | 0.11             | 0.11             |

### Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the applications referred to above and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contact office, or via the Internet. This product should not be used for purposes other than the applications referred to above. If disposing of used product, take care to protect the environment.

05-2020

ExxonMobil (China) Investment Co. Ltd

29.05.2020

17th Floor, Metro Tower  
30 Tian Yao Qiao Road  
Shanghai 2000030  
China

+86 21 24076000

<http://www.exxonmobil.com>

Typical Properties are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local ExxonMobil contact or visit [www.exxonmobil.com](http://www.exxonmobil.com)

ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil-affiliate entities.

Energy lives here™

**ExxonMobil**

Exxon Mobil  

© Copyright 2003-2019 Exxon Mobil Corporation. All Rights Reserved